Safety Data Sheet

					• •		
		Se	ection 1 - Pr	oduct Infor	mation	ı	
Product Name	e: ARJOSOUND					Supplier:	ArjoHuntleigh, Inc
Product Code	duct Code Number: 0823 Information Ph			none: 1-800-323-1245			2349 West Lake Street
,			ntact: CHEMTREC 1-800-424-9300				Addison, IL 60101
		Se	ection 2 - Ha	zard Identi	fication		
Does not cont	ain sufficient quantities of hazards						
			Section 2.1	- Label Eler			
	Hazard Pictograms					itionary Stateme	
			Use general che	emical hygiene _l	practices when v	vorking with che	micals. Avoid eye contact.
Signal Word: N	None]				
	Hazard Statements:						
	May cause mild eye irritation						
			Section 3	- Composit	tion		
	Chemical Name			CA	AS#		Percent w/w
Poly Sorbate 2	20			9005	5-64-5		50
Propylene Gly	col			57-	-55-6		3
		9	Section 4 - F	irst Aid Me	asures		
	f with plenty of water.			irst Aid Me	asures		
	f with plenty of water. th plenty of water. If irritation occu			irst Aid Me	asures		
Eyes: Flush wi		rs consult a physici	an				
Eyes: Flush wingestion: Rins	th plenty of water. If irritation occu	rs consult a physici	an				
Eyes: Flush wingestion: Rins	th plenty of water. If irritation occu se mouth and throat with water. Di	rs consult a physici ink water to dilute	ian material. Conta	ct a physician if	you feel unwell.		
Eyes: Flush wingestion: Rins	th plenty of water. If irritation occu se mouth and throat with water. Di	rs consult a physici ink water to dilute	an	ct a physician if	you feel unwell. Hazard Dat		
Eyes: Flush wingestion: Rins	th plenty of water. If irritation occu se mouth and throat with water. Di	rs consult a physici ink water to dilute Section	ian material. Conta	ct a physician if	you feel unwell. Hazard Dat Special Fire Fig	hting Procedure	es: Avoid exposure to fumes or vapors.
Eyes: Flush wingestion: Rinsnhalation: No	th plenty of water. If irritation occu se mouth and throat with water. Do bt a likely source of contamination.	rs consult a physici ink water to dilute Section Ex Use extinguishi	material. Contains 15 - Fire and tinguishing Meding media suitab	ct a physician if d Explosion dia: le for	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont	hting Procedure ained positive pr	essurized breathing apparatus
Eyes: Flush wingestion: Ring nhalation: No	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA	rs consult a physici ink water to dilute Section Ex Use extinguishi	material. Contains 5 - Fire and citinguishing Medical	ct a physician if d Explosion dia: le for	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A	hting Procedure ained positive pr Approved or equ	
eyes: Flush wingestion: Ring nhalation: No	th plenty of water. If irritation occurse mouth and throat with water. Do to a likely source of contamination. Limits	rs consult a physici ink water to dilute Section Ex Use extinguishi	material. Contains 15 - Fire and tinguishing Meding media suitab	ct a physician if d Explosion dia: le for	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A	hting Procedure ained positive pr Approved or equ	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
eyes: Flush wingestion: Ring nhalation: No	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA	Section Section Ex Use extinguishing many and a common surrounding many and a common surrounding many areas areas and a common surrounding many areas areas and a common surrounding many areas and a common surrounding many areas areas and a common surrounding many areas areas areas and a common surrounding many areas areas areas areas and a common surrounding many areas are	material. Contain 15 - Fire and tinguishing Meding media suitab aterial. Product	ct a physician if d Explosion dia: le for will not burn.	you feel unwell. Hazard Date Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling.	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
eyes: Flush wingestion: Ring nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Use extinguishing surrounding management.	material. Contains 15 - Fire and citinguishing Media suitab aterial. Product on 6 - Accide	ct a physician if d Explosion dia: lle for will not burn.	you feel unwell. Hazard Date Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling.	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
eyes: Flush wingestion: Ring nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA	Section Use extinguishing surrounding management.	material. Contains 15 - Fire and citinguishing Media suitab aterial. Product on 6 - Accide	ct a physician if d Explosion dia: lle for will not burn.	you feel unwell. Hazard Date Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling.	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
Eyes: Flush wingestion: Rins nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Use extinguishing surrounding management.	material. Contains 15 - Fire and citinguishing Media suitab aterial. Product on 6 - Accide	ct a physician if d Explosion dia: lle for will not burn.	you feel unwell. Hazard Date Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling.	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
eyes: Flush wingestion: Ring nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Use extinguishing surrounding management.	material. Contains 15 - Fire and citinguishing Media suitab aterial. Product on 6 - Accide	ct a physician if d Explosion dia: lle for will not burn.	you feel unwell. Hazard Date Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling.	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
eyes: Flush wingestion: Ring nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Section Use extinguishis surrounding management of the slippery	material. Contains 15 - Fire and citinguishing Media suitab aterial. Product on 6 - Accide	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls.	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. E Measures	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
Eyes: Flush wingestion: Rins nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Use extinguishis surrounding management of the slippery	material. Contains and the section 7 - Ha	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls.	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. E Measures	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
Eyes: Flush wingestion: Rins nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Use extinguishis surrounding management of the slippery	material. Contains and the section 7 - Ha	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls.	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. E Measures	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
eyes: Flush wingestion: Rins nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA	Section Section Ex Use extinguishing many Section Se	material. Contains and the second of the sec	ct a physician if d Explosion dia: lle for will not burn. ental Releas oid falls.	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. The Measures Storage	hting Procedure ained positive pr Approved or equ IZARD: Product v	essurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE
Eyes: Flush wingestion: Rins nhalation: No Flash Point: > 150°C Mop up or flus ntended for in	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA uel: NA uel: not for consumer of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water. Flent is a second of the plenty of water.	Section Section Ex Use extinguishis surrounding many or will be slippery	material. Contains and the section 7 - Ha	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls. andling and container.	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. The Measures Storage	hting Procedure ained positive pr Approved or equ IZARD: Product	ressurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE will not burn but may splatter if heated t
Eyes: Flush wingestion: Rins nhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA USEL: NA OSHA PEL:	Section Section Ex Use extinguishing surrounding many Section Our will be slippery Section ACGIH TLV	material. Contains and the string media suitable aterial. Product of the string media suitable aterial aterial suitable aterial suita	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls. endling and container. posure Cont	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. The Measures Storage	hting Procedure ained positive pr Approved or equ IZARD: Product	ressurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE will not burn but may splatter if heated t
Eyes: Flush wi Ingestion: Rins Inhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA USEL: NA OSHA PEL:	Section Section Ex Use extinguishis surrounding many or will be slippery	material. Containing media suitable aterial. Product of the containing media suitable aterial suitable aterial suitable aterial. Product of the containing media suitable aterial suit	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls. andling and container. posure Cont ppe Not required	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. The Measures Storage	hting Procedure ained positive pr Approved or equ IZARD: Product v	ressurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE will not burn but may splatter if heated to meral Hygiene Considerations: rdance with good industrial hygiene and
Eyes: Flush wi Ingestion: Rins Inhalation: No Flash Point: > 150°C	th plenty of water. If irritation occurse mouth and throat with water. Do not a likely source of contamination. Limits LEL: NA UEL: NA USEL: NA OSHA PEL:	Section Section Ex Use extinguishing surrounding many Section Our will be slippery Section ACGIH TLV	material. Containing Meding media suitable aterial. Product of the containing media suitable aterial suitable ater	ct a physician if d Explosion dia: le for will not burn. ental Releas oid falls. endling and container. posure Cont	you feel unwell. Hazard Dat Special Fire Fig Wear self-cont MSHA/NIOSH A EXPLOSION HA boiling. The Measures Storage	hting Procedure ained positive pr Approved or equ IZARD: Product v Ge Handle in acco	ressurized breathing apparatus ivalent to maintain TLV. UNUSUAL FIRE will not burn but may splatter if heated t

Ventilation Normal room ventilation

			Section	9 - Physical	and Chemic	cal Properti	es		
Appearance	odor	odor threshold	рН	Melting Point	Boiling point	Evaporation rate	Flammability	Upper/lower flammability limits	Vapor pressure
llue Liquid	Eucalyptus	NE	5	NE	212ºF	NE	none	NA/NA	17mm F
/apor Density (air = 1)	Density (lbs/gal)	Specific Gravity	pH(use dil)	Solubility (in water)	Partition coefficient	Auto Ignition temp	Viscosity	Decomposition Temp	
0.62	8.75	1.05	7	100%	NE	NE	viscous	NE	
			Sec	tion 10 - Sta	bility and R	Reactivity			
carbon oxides a	nd nitrous oxid	es will evolve.							
			Secti	on 11- Toxi	cological In	formation			
ingre	dient	Acute toxicity(oral LD50) rat	Acute toxicity(derm. LD50)rabbit	Skin and Eye	Carcinogen	Mutagen	Reproduct. Toxicity	STOST -single Exposure	STOST Repeated exposure
Poly Sorbate 20	ı	36700μL/kg	NE	Mild eye irritant	no	no	none	none	none
Propylene Glycol		> 5000mg/kg 2 - Ecological In	>2000mg/kg	not an irritant	no	no	none	none al Considerations	none
No information	available				I .	•	is not consider i	to be a hazardous waste. D cions.	ispose of in
			Sec	tion 14 - Tra	ansport Info	ormation			
UN number			Basic Descrip		•		Class	Packing Group	LTD QT
			Not Regulated						
		•	under sections	, ,	of Title III of the	e Superfund ame		eauthorization Act of 1986. 72, and 40 CFR part 68	
			S	ection 16 - (Other Infor	mation			
VHMIS:		I	3	•	Health - 1	Flam 0	R - 0	PPE- A	
Date Prepared:	04-20-2015	1			nvironmental, F				
								he information given is des	