

SPECIFICATION SHEET

Prioma® Medical Bed 500



**Affordable,
essential
everyday
care**

Standard Features

- Safe Working Load (SWL) 250 Kg
- Tente 125mm single central locking castors
- Foot end central lock pedals
- Linak actuators
- ABS removable deck panels
- Full length split side rails
- ACOM cabled hook over attendant control panel
- Retracting backrest
- Manual CPR backrest quick release
- Foot/calf elevation - manually operated
- Urine bag hooks and strap rail - both sides of bed
- Four accessory sockets
- Soft contoured mattress retainer handles
- Removable, lightweight head and foot panels
- Head and foot end rotating wall buffers
- Trendelenburg & reverse Trendelenburg tilt 14°

Model pictured with 3/4 length split side rails.



Optional Features

- Tente 125mm individual locking castors
- Tente 125mm twin central locking castors
- Tente 150mm twin central locking castors
- 5th wheel
- Head end central lock foot pedals³
- 3/4 length split side rails
- Battery back up unit
- Attendant Control Panel (ACP)¹
- HB70 Patient handset
- HB70 Nurse handset
- Under bed light (set in permanent on-mode)
- Integral bed extension - 285mm extension
- Integral linen rack - 300mm extension²
- Lockable head and foot panels
- Range of accessories

Basic Dimensions

Overall length	2150 mm
Overall length base extension extended	2435 mm
Linen rack extension	300 mm
Overall width	1000 mm (+/- 5mm)
In bed dimensions - inside panel to inside panel	2030 mm (I)
Recommended mattress size - width	870 mm (w)
Deck height range - Tente 125mm single central locking castors	380 mm to 835 mm (+/- 5mm)
Trendelenburg and reverse Trendelenburg tilt - electronic	0 to 14°
Backrest angle adjustment - electronic	0 to 70°
Knee break angle adjustment - electronic	0 to 35°

Product Weight (approximate)

Includes full length drop down ABS side rails fitted	146 Kg
Safe Working Load (SWL)	250 Kg
Maximum patient weight	185 Kg

Electrical Data

Power in - switch mode operating voltage range 100V to 240V - 50/60Hz

Duty rating - intermittent 10%, max 2 min / 18 min

Electric shock protection - Class 1 Type B

Liquid ingress protection - IP54

Internally powered equipment - battery backup only - 2 x 12V series connected batteries, sealed chargeable lead/acid gel 1.2 amp hours

¹ ACP attendant control panel only available as an alternative to ACOM cabled hook over control panel.

² Only available with built in bed extension.

³ Feature only available if central locking castors are fitted.

At Arjo, we are committed to improving the everyday lives of people affected by reduced mobility and age-related health challenges. With products and solutions that ensure ergonomic patient handling, personal hygiene, disinfection, diagnostics, and the effective prevention of pressure ulcers and venous thromboembolism, we help professionals across care environments to continually raise the standard of safe and dignified care. Everything we do, we do with people in mind. www.arjo.com

Arjo AB, Hans Michelsensgatan 10, SE-211 20 Malmö, Sweden. Phone: +46 (0) 10 335 45 00

www.arjo.com